

JLT CLAMPS

PRESSURIZED GLUE TANK FOR PVA GLUE



Includes:

- Chrome-plated brass lid with an anti-corrosion coated heavy-duty steel tank and bottom (9001)
- AISI 304/316 stainless steel tank, bottom and lid (9012)
- Convenient carry handle
- Straight grip glue gun with standard point nozzle
- 10' nylon hose
- Glue gun housing with support
- Inner plastic glue container
- Nylon adapter for flushing of system

Highlights:

- Process: Fill container with glue, pressurize to 75psi, shut-off the ball valve and remove the air supply. Glue is then dispensed by extrusion using the gun and is empty once the tank pressure reaches 0 psi.
- Efficient: Adjustable flow glue gun, optional nozzles and expandable to (3) guns on one tank.
- Applications: door parts, edge gluing, dowel holes, grooves, edges, dados, biscuit joints etc.
- Low maintenance: no daily or weekly cleaning required.
- Convenient: keeps glue fresh for months and is always ready for use anywhere it is needed.

Specifications:

	9001 (A8)	9012 (D12)
Max Pressure	8 bar / 75psi	8 bar / 75psi
Glue Capacity	8kg / 1.5 gallons	12kg / 2.5 gallons
Dimensions	20x20x65cm H 8x8x25.5"H	25x25x65cm H 10x10x25.5"H
Weight	14kg / 30lbs.	14kg / 30lbs.



Guide for universal nozzle
(optional accessory)



Gluing cylinder with rubber
roller (optional accessory)



Adjustable nozzle for edge
gluing (optional accessory)